

Material safety data sheet summary for 'Rapid Coat' preservative

MSDS: 'Rapid Coat'	
Description	A light organic solvent preservative treatment.
First aid	Swallowed: do not induce vomiting – give glass of water. Eye contact: flush with water for 15 mins and contact doctor. Skin contact: wash with soapy water and remove contaminated clothing. Inhaled: remove person to fresh air, keep warm and at rest.
Recommended PPE	Chemical goggles; rubber gloves; respirator with Type A-P filter
Handling precautions	Keep away from sources of ignition. Use only in a well ventilated area. Do not empty into drains. Keep container tightly closed.
Minor spills	Remove ignition source. Clean up the spill immediately. Contain small quantities with sand, earth or vermiculite. Collect residues and seal in a labelled container for later disposal.
Major spills	Evacuate the area and alert the fire brigade. Remove all ignition sources. Wear breathing apparatus and gloves. Prevent spillage from entering drains or water courses. Collect residue and seal in a labelled drum.
Disposal	Consult the distributor for recycling options. Consult the local waste management authority for disposal information.
Storage and transport	Classified as: Dangerous Goods Class 3. Label required: Flammable Liquid. Store in original container under cool, dry conditions, away from sources of ignition and incompatible chemicals. Keep container sealed.
Flammability	Class 3 – high flammable. Extinguish fire with carbon dioxide, dry chemical powder or foam extinguisher.